

GENERAL DESCRIPTION:

Cavity Tappers are used for combining antennas to obtain particular radiation patterns or to set up indoor distribution networks. They are available to cover multi-band frequencies over 800-2200 MHz and are of coaxial line transformation type. They are designed for low insertion loss, high power rating and compact in size. Flexibility in the choice of connectors is provided.



FEATURES:

- High power rating
- Suitable for indoor and outdoor applications
- Multi band versions for 800-2200 MHz
- Low insertion loss
- Compact size

APPLICATIONS:

- Indoor distribution networks
- Combining antennas

SPECIFICATIONS:

Frequency range	800-2200 MHz
Power handling	200 W
Insertion loss (Port 1)	<1.2 dB (Max.)
Coupling (Port 2)	7.0 dB
VSWR	<1.5
Impedance	50 Ω
For connecting antennas	2
Connector type	N - Female
Weight (approx.)	500 gm
Max. size (L x W x H)	246 x 65.0 x 25.4 mm
Material	Housing : Aluminum Inner conductor : Brass

Avantel Softech Limited

Plot No. 16, Sector-III, Madhapur, Hyderabad - 500 081, India.
Tel : +91-40-2311 2231 Fax : +91-40-2311 2336
E-mail: marketing@avantelsoftech.com

Vedang Radio Technology Pvt. Ltd.

105, Nirman Industrial Estate, Link Road, Malad (West)
Mumbai - 400064, Maharashtra (India)
Phone:(22)-28788001 Fax: (22)-28788002