

## Specifications:

Power Output	:	+ 19 dBm
No of Humps	:	2 Humps in each band
Hump Size	:	As per customer requirement
Pass Band Gain	:	60 dB (typ)
Gain Flatness	:	± 1 dB
Gain Adjustment	:	1 dB steps
Noise Figure	:	6 dB
Group Delay	:	< 3.8 μSec
In/Out Impedance	:	50 ohms
Return Loss	:	>10 dB (13 dB Typ)
RF Connectors	:	N - Female
Supply Voltage	:	90 - 260 V Ac, 50 ± 3 Hz
Operating temperature	:	0° to +50° C
Field tune ability of frequency	:	Yes
Environment of usage	:	In-doors



### Manufactured By :

#### Avantel Softech Limited

Plot No. 16, Sector-III, HUDA Techno Enclave, Opp. V.S.N.L,  
Madhapur, Hyderabad - 500 081, India.

Tel : +91-40-2550 4056/57/58 Fax : +91-40-2311 2336

E-mail: marketing@avantelsoftech.com www.avantelsoftech.com

### Marketed By :

#### Vedang Radio Technology Pvt Ltd

105,Nirman Industrial Estate Link Road, Malad (WEST)  
Mumbai-400064, Maharashtra, India.

Phone:(22)-28788001 Fax: (22)-28788002

sales@vedangradio.com  
www.vedangradio.com