

Specifications:

Power Output	:	+ 19 dBm
No of Humps	:	1 Hump
Hump Size	:	As per customer requirement
Pass Band Gain	:	60 dB (typ)
Gain Flatness	:	± 1 dB
Gain Adjustment	:	1 dB steps
Noise Figure	:	6 dB
Group Delay	:	< 3.8 µSec
In/Out Impedance	:	50 ohms
Return Loss	:	>10 dB (13 dB Typ)
RF Connectors	:	N - Female
Supply Voltage	:	90 - 260 V Ac, 50 ± 3 Hz
Operating temperature	:	0° to +50° C
Field tunability of frequency	:	Yes
Hump Expansion	:	Yes (One hump can be expanded to two humps at cost)
Environment of usage	:	In-Doors



Manufactured By :

Avantel Softech Limited

Plot No. 16, Sector-III, HUDA Techno Enclave, Opp. V.S.N.L,
Madhapur, Hyderabad - 500 081, India.

Tel : +91-40-2550 4056/57/58 Fax : +91-40-2311 2336

E-mail: marketing@avantelsoftech.com www.avantelsoftech.com

Marketed By :

Vedang Radio Technology Pvt Ltd

105,Nirman Industrial Estate Link Road, Malad (WEST)
Mumbai-400064, Maharashtra, India.

Phone:(22)-28788001 Fax: (22)-28788002

sales@vedangradio.com
www.vedangradio.com