

**Band Pass Filter [GSM Killer]**  
[Model No: VR-BF-856-D64]

*Vedang* Band Pass Filter is high performance equipment used to reduce the interference on account of leakages from CDMA BTS in GSM 900 band. CDMA Masks (transmit band) does not provide sufficient rejection for GSM uplink Band. This filter needs to be placed at the output of CDMA BTS to arrest in-band leakage in GSM uplink. This filter is for CDMA operators with frequency allocation on the left of 888MHz.

- Low Insertion Loss
- High Rejection at critical spots through customized design
- Excellent return loss

**Specifications:**

Pass Band Frequency	824 – 888 MHz
Pass Band Insertion Loss	
888 MHz	2.0 dB (Typical)
887 MHz	1.5 dB (Typical)
884 MHz	1.0 dB (Typical)
824-869 MHz	0.65 dB (Typical)
Rejection	
890 MHz	30 dB
891 MHz	40 dB
>892 MHz	50 dB
Return Loss	18 dB (Min)
Impedance	50 Ω
Operating Temperature	-10° C – +55° C
Connector Type	DIN (F)
Environment	Indoor
Weight	3.0 Kg (Appx.)
Dimensions	157 x 120 x 100 mm (Appx.)

---

**Vedang Radio Technology Pvt Ltd**

313-314, Orbit Industrial Estate, Off Link Road, Malad (West), Mumbai-400064, Maharashtra, India  
Phone: (22)-28788001 Fax: (22)-28788002 E-mail: [sales@vedangradio.com](mailto:sales@vedangradio.com) [www.vedangradio.com](http://www.vedangradio.com)